

U.S. Application No. 09/825,909
Group Art Unit: 3762**AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application.

Please cancel claims 8-13 without prejudice or disclaimer as to the subject matter thereof.

Listing of Claims:

1. (currently amended) A system comprising:
at least one implantable medical device ("IMD") providing therapy delivery, said
IMD including a processor controlling the delivery of therapy to a patient; and
an external sensor module having at least one physiological sensor adapted to
operatively couple to a surface portion of a peripheral limb of the patient and
operational to continuously collect physiological data of the patient; and
wherein said external sensor module continuously transmits the
continuously collected physiological data ~~signals~~ to the IMD;
wherein said IMD processor ~~processes~~ ing the physiological data to produce
therapy delivery control signals in implementation of dynamic, closed-loop
self-monitoring therapy delivery.
2. (currently amended) The system of claim 1 wherein said at least one IMD
comprises ~~selected from the group consisting of a pacemaker, a defibrillator, a drug~~
~~pump, and a neurological stimulator.~~
3. (previously amended) The system of claim 1 wherein said external sensor
module is selected from the group consisting of: a wristwatch, a ring, a patch, and a
sock.
4. (previously amended) The system of claim 1 wherein said external sensor
module transmits the ~~collected~~ physiological data ~~signals~~ to the IMD over a
communication channel including RF signals.

5. (previously amended) The system of claim 1 wherein said physiological sensor is one selected from the group consisting of: a pressure sensor, an oxygen saturation sensor, a cardiac acceleration sensor, a flow sensor, a heart auscultation sensor, and intracardiac transthoracic impedance sensor.

6.-13. (canceled)

14. (new) A method, comprising:
providing therapy delivery using at least one implantable medical device ("IMD"),
said IMD including a processor controlling the delivery of therapy to a patient;
and
continuously collecting physiological data of the patient using an external sensor
module having at least one physiological sensor;
continuously transmitting the physiological data from said external sensor
module to the IMD; and
processing the physiological data to produce one or more therapy delivery
control signals in a dynamic, closed-loop, self-monitoring therapy delivery
regime.

15. (new) A method according to claim 14, wherein said at least one IMD comprises a pacemaker.

16. (new) A method according to claim 14, wherein said external sensor module comprises at least a one of: a wristwatch, a ring, a patch, a sock.

17. (new) A method according to claim 14, wherein said external sensor module transmits the physiological data to the IMD over a communication channel including RF signals.

U.S. Application No. 09/825,909
Group Art Unit: 3762

18. (new) A method according to claim 14, wherein said at least one physiological sensor comprises a one of: a pressure sensor, an oxygen saturation sensor, a cardiac acceleration sensor, a flow sensor, a heart auscultation sensor, a transthoracic impedance sensing apparatus.
19. (currently amended) A computer readable medium for storing instructions for performing a method, comprising:
- instructions for delivering a therapy via at least one implantable medical device ("IMD"), said IMD including a processor controlling the delivery of therapy to a patient;
 - instructions for automatically collecting physiological data of the patient using an external sensor module having at least one physiological sensor;
 - instructions for continuously transmitting the collected physiological data from said external sensor module to the IMD; and
 - instructions for processing the collected physiological data to produce one or more therapy delivery control signals in a dynamic, closed-loop, self-monitoring therapy delivery regime.
20. (new) A system according to claim 1, wherein said IMD comprises at least one of the group: a defibrillator, a drug pump, a neurological stimulator, a deep brain stimulator, a cochlear assist device.
21. (new) A system according to claim 1, wherein the at least one physiologic sensor comprises at least two of the group: a piezoelectric sensor, an LED-based sensor, a surface conductivity sensor, a vibratory sensor, a pressure sensor, an oxygen saturation sensor, an impedance sensor.
22. (new) A system according to claim 21, further comprising a switching means for alternating the respective operating cycles of the at least two sensors to reduce operating interference between said at least two sensors.

U.S. Application No. 09/825,909

Group Art Unit: 3762

23. (new) A system according to claim 21, further comprising a sensor interface disposed adjacent each of the at least two sensors, wherein said sensor interface comprises one of the group: a gel material, a fluid material, an adhesive material, a rubber material, a foam material.

24. (new) A system according to claim 21, wherein one of the at least two sensors is adapted to couple continuously around the peripheral limb of the patient.